

# Appliance Edition

## General Specifications



Appliances	P520	P550	P560	P570
Base Users / Max Users	20	50	100 / 200	300 / 500
Max Concurrent Calls	10	25	30 / 60	60 / 120
Base / Max Call Center Agents	20	50	100 / 200	300 / 500
Max FXS Ports	4	8	8	16
Max FXO/BRI Ports	4	8	8	16
Max GSM/3G/4G Ports	1	4	4	6
Max E1/T1/J1 Ports	-	-	1	2
Expandable D30	-	0	1	2
NFC Read/Write	No	Yes	Yes	Yes
Ethernet Interfaces	2 x 10/100 Mbps	2 x (10/100/1000 Mbps)		
Hard Disk	-	No	1 SATA (Up to 2TB)	
USB	-	1 (USB Portable SSD, Up to 2TB) (USB Flash Drive, Up to 256)		
Power Supply	DC 12V 1A	AC 100-240V 50/60HZ 0.6A max	AC 100-240V 50/60HZ 1.5A max	
Size (L x W x H) (cm)	16 x 16 x 3	34 x 21 x 4.4	44 x 25.2 x 4.4	44 x 25.2 x 4.4
Weight	0.3 KG	1.64 KG	2.37 KG	2.38 KG
Form Factor	Desktop & Wall-mount	1U Rackmount		
Environment	Operation Range: 0°C to 40°C, 32°F to 104°F Storage Range: -20°C to 65°C, -4°F to 149°F Humidity: 10-90% non-condensing			

\* The availability of the P520 PBX model is subject to regional sales policy.